



A Global Leading IoT Terminals And Wireless Data Solutions Provider

MeiG-SLM500L

多网络制式 Smart LTE 模块

支持 Wi-Fi & BT 功能

✓

✓

✓

✓

✓

✓



SLM500L-C
LTE FDD: B1/B3/B5/B8
LTE TDD: B34/B38/B39/B40/B41
WCDMA: B1/B8
TD-SCDMA: B34/B39
EVDO/CDMA: BC0
GSM: 900/1800MHz
SLM500L-E
LTE FDD: B1/B3/B5/B7/B8/B20/B28A
LTE TDD: B38/B40/B41
WCDMA: B1/B5/B8
GSM: 850/900/1800/1900MHz
SLM500L-A*
LTE FDD: B2/B4/B5/B7/B12/B13/B17/B25/B26/B66
WCDMA: B2/B4/B5/B8
GSM: 850/1900MHz
SLM500L-AU*
LTE FDD: B1/B3/B5/B7/B8/B28
LTE TDD: B40
WCDMA: B1/B5/B8
GSM: 850/900/1800MHz
SLM500L-J*
LTE FDD: B1/B3/B8/B18/B19/B26
LTE TDD: B41
WCDMA: B1/B6/B8/B19
SLM500L-LA*
LTE-FDD: B2/B4/B5/B7/B8/B25/B28/B66
LTE TDD: B40
WCDMA: B2/B5/B8
GSM: 850/900/1900MHz
SNM500L
Wi-Fi & BT

1X Advanced: 307.2Kbps (DL/UL)
GSM:
GPRS: 107Kbps (DL)/85.6Kbps (UL)
EDGE: 236.8Kbps (DL)/236.8Kbps (UL)
3.55V~4.4V 3.8V
Class 4 (33dBm±2dB) for GSM850
Class 4 (33dBm±2dB) for EGSM900
Class 1 (30dBm±2dB) for DCS1800
Class 1 (30dBm±2dB) for PCS1900
Class E2 (27dBm±3dB) for GSM850 8-PSK
Class E2 (27dBm±3dB) for EGSM900 8-PSK
Class E2 (26dBm±3dB) for DCS1800 8-PSK
Class E2 (26dBm±3dB) for PCS1900 8-PSK
Class 3 (24dBm+1/-3dB) for WCDMA bands
Class 3 (24dBm+3/-1dB) for EVDO/CDMA BC0
Class 2 (24dBm+1/-3dB) for TD-SCDM

LTE:
Cat 4 FDD: 150Mbps (DL)/50Mbps (UL)
Cat 4 TDD: 117Mbps (DL)/30Mbps (UL)
UMTS:
DC-USDPA: 42Mbps (DL)
HSUPA: 5.76Mbps (UL)
WCDMA: 384Kbps (DL/UL)
TD-SCDMA:
4.2Mbps (DL)/2.2Mbps (UL)
CDMA2000:
EVDO: 3.1Mbps (DL)/1.8Mbps (UL)